

W. JOHN NUSKE, CHAIRMAN
ROGER GRINER, VICE CHAIR
ROBERT ROSA, MEMBER
ROBERT WEAVER, MANAGER



11318 MAIN STREET
P. O. BOX 68
HONOR, MI 49640-0068
(231) 325-3051
(231) 325-2767 FAX

Your Local Road Professionals

WELL SITE DRIVEWAYS

Definition:

Any driveway providing access to land which will be used for oil or gas exploration. The intent of designating a use as a Well Site Driveway is to define those uses which would require wider access for large vehicles. In the event of a dispute over whether or not a specific use will be designated as Well Site Driveway the Board of County Road Commissioners will make the final determination and will base their decision on this intent.

Width:

1. All Well Site Driveways will have a **minimum width of 20 feet**, measured at right-angles to the centerline of the driveway at the right-of-way line. Increased width to accommodate large commercial and industrial sites will be permitted at the discretion of the county highway engineer.
2. All Well Site Driveways will meet the traveled way with a curve with a **minimum radius of 30 feet**.

Location:

1. No portion of a Well Site Driveway, including the curve which meets the traveled way, will extend beyond the property line of an adjoining parcel of property.
2. No portion of a Well Site Driveway, including the curve which meets the traveled way, will be located closer than 50 feet to the nearest right-of-way line of an intersecting road or street.
3. No driveway will be allowed when the sight distance of approaching vehicles is less than the safe stopping distance.
4. If a Well Site has access to a private road as well as an existing county road **the driveway will not be permitted** on the existing county road

Angled Driveways:

When the property owner wishes to construct a Well Site Driveway at other than 90° to the centerline of the roadway to facilitate ingress and egress of traffic, the near side of the driveway on the right as approaching will not have less than 45° angle with the centerline of the road and the far side of the driveway on the right as approaching will not have less than 60° angle with the centerline.

Surface:

The surface shall be equal to or better than the following:

6 inch compacted processed 22A or 23A road gravel.

General:

1. Whenever there is an existing ditch or the Board of County Road Commissioners or its agents install a ditch prior to the construction of any tube or driveway, the county highway engineer will determine whether or not a culvert is required and if so the size (diameter) and length of the culvert required, and the property owner shall furnish and install the culvert so determined.
2. Culverts will be installed in line with and on the same grade as the road ditch.
3. No culvert of less than a 12" diameter may be installed.
4. All culverts will be concrete pipe or corrugated metal pipe.
5. If the property owner wishes to use alternate materials the county highway engineer will determine whether the materials are equal to or better than those above before purchasing or installing.
6. If the Well Site Drive slopes toward the road 2% or more, construct a ridge as indicated on the attached drawing to divert runoff away from the public road.

Fees

There will be a fee of seventy five dollars (**\$75.00**) for all Well Site Driveway Permits.

Adopted at the regular meeting, at which time a hearing was held, on **June 25, 2008**, in accordance with Act 212, of the Acts of 1980.